# Color LCD Signature Pad STU-540/STU-541



## Signature pads with state-of-the-art encryption providing industry-leading security

Positioned as Wacom's top-of-the-line, in addition to the existing signature pads, STU-540 and STU-541 are 5" color LCD signature pads designed to capture handwritten eSignature with the highest security.

For those who are interested in enhancing their paperless workflows by saving time of transaction, reducing costs of operation and improving customer service more securely, STU-540 and STU-541 are the right solution.



## STU-540 | STU-541

- 5 inch (800 x 480 pixels) thin and light, color LCD signature pad
- Hardened cover glass with anti-glare treatment provides a signing surface with natural paper-like feeling
- Easy connection via USB
- VCP mode is supported for virtual computing environment
- Highest-level of security by state-of-the-art encryption
  - TLS (Transfer Layer Security) encryption (STU-540)
  - AES256/RSA2048 encryption (STU-541)
- Serial connectivity is available as an optional extra (STU-540)

#### Software Development Kit

STU SDK is available for connecting Wacom signature pads with customers application.

#### Usage

- Input eSignature to confirm transactions or provide consent at a banking counter, retail store, hospital
- Show promotional images and messages when the pad is on stand-by
- Select currency, a credit card type or transaction type (customizable)

# Color LCD Signature Pad STU-540/STU-541



#### Features

- Patented cordless, battery-free pen with 1024 levels of pressure sensitivity to accurately capture the unique signature including biometric data
- The most secure TLS encryption (STU-541) and state-of-the-art RSA/AES encryption (STU-540) to perform secure transactions
- VCP mode is supported to be compatible with Citrix XenDesktop and XenApp v6.5 and later
- Key pad and PIN pad are customizable to any currency or transaction type
- The display can also be used for advertising, promotions or branding logo as well. The pads have internal memory for image storage to serve this function.

wacor	TY • 38	UR 1,471,00 90.42 FURD LEN IFY 05.92 AUD	
-			
AUD			
0.1	2 3 4 5		
01	2345		
01 1 4			Gore
01 1 4 7	2345	6789	**.

General Specifications	STU-540	STU-541		
Overall dimensions	163 x 157 x 10 mm (6.41 x 6.18 x 0.39 inch)			
Weight	250 g (0.55 lbs.)			
Main body color	Black			
Power supply	USB bus powered			
Power consumption	2.5W maximum			
Communication interface	USB/RS-232	USB		
Protocol modes	USB/VCP/RS-232	USB/VCP		
LCD Display				
Display type	Amorphous <sup>-</sup>	IFT LCD		
Cover plate surface	AG etched glass			
Screen size	5" (108 x 65 mm)			
Native resolution	800 x 480	pixels		
Pad and pen				
Reading technology	Electromagnetic Resonance (EMR)			
Active area	108 x 65 mm (4.2	5 x 2.56 inch)		
Coordinate resolution	2,540 lpi / 0.01 mm/pt(non-interpolated)			
Coordinate accuracy	± 0.5mm (center)			
Pen report rate	200 points per second (non-interpolated)			
		(non-interpolated)		
Pen pressure levels	1024 (non-inte			
Pen pressure levels Encryption				
1	1024 (non-inte	erpolated)		
Encryption	1024 (non-inte	erpolated)		
Encryption Miscellaneous Pen storage	1024 (non-inte AES256 / RSA2048	erpolated)		
Encryption Miscellaneous	1024 (non-inte AES256 / RSA2048 Pen compartment	TLS		

Operating temperature, relative humidity	+5°C to +40°C, +41°F to +104°F, (humidity 30% to 80% RH, no condensing)
Storage temperature, relative humidity	-20°C to +60°C, -4°F to +140°F, (humidity 30% to 90% RH, no condensing)
Package Content	Signature pad, cordless and battery-free pen, USB cable (3 m / 9.84 ft), quick start gui- de, pen tether (nylon fiber, 50 cm / 19.7 inch) Signature pad, pen, USB cable, pen tether, Quick Start Guide
Optional Accessories	Pen, Nibs (5pcs) and removal tool, Hybrid USB cable (3m), Pen tether, Serial Kit (for STU-540)