



Datasheet UACC-OM-MM-10G-D/1G-D



Multi-mode Optical Module

UACC-OM-MM-10G-D:

Multi-mode, duplex, fiber transceiver module.

The 10 Gbps Multi-mode Optical Module is a duplex transceiver that delivers up to 10 Gbps speed over distances up to 300 meters.

UACC-OM-MM-1G-D:

Multi-mode, duplex, fiber transceiver module.

The 1 Gbps Multi-mode Optical Module is a duplex transceiver that delivers up to 1.25 Gbps speed over distances up to 550 meters.



UACC-OM-MM-10G-D

Supported Media	Multi-Mode Fiber
Connector Type	(2) LC
TX Wavelength	Black Latch: 850 nm
RX Wavelength	Black Latch: 850 nm
Data Rate	10 Gbps
Max. Power Consumption	0.8W
Cable Distance	300 m
Operating Temperature	0 to 70° C (32 to 158° F)
Pack Options	2-pack, 20-pack
WARNING	CLASS 1 LASER PRODUCT, IEC/EN 60825-1:2014 – Do not look into the ends of the fiber optic cable or SFP module while converters are powered.

UACC-OM-MM-1G-D

Supported Media	Multi-Mode Fiber
Connector Type	(2) LC
TX Wavelength	Black Latch: 850 nm
RX Wavelength	Black Latch: 850 nm
Data Rate	1.25 Gbps
Max. Power Consumption	0.66W
Cable Distance	550 m
Operating Temperature	0 to 70° C (32 to 158° F)
Pack Options	2-pack, 20-pack
WARNING	CLASS 1 LASER PRODUCT, IEC/EN 60825-1:2014 – Do not look into the ends of the fiber optic cable or SFP module while converters are powered.



Specifications are subject to change. Ubiquiti products are sold with a limited warranty described at www.ui.com/support/warranty

©2021 Ubiquiti Inc. All rights reserved. Ubiquiti, Ubiquiti Networks, the Ubiquiti U logo, the Ubiquiti beam logo, UniFi, and UniFi Network are trademarks or registered trademarks of Ubiquiti Inc. in the United States and in other countries. All other trademarks are the property of their respective owners.